

TRANSFORM

ULTRA ABSORBENT

SUNRISE has combined break-through technology with 100% recycled materials to create **TRANSFORM**. This incredibly absorbent material out performs, clay, cellulose, vermiculite, powders, peat moss and other similar absorbent substances. **TRANSFORM** is ideal for the cleanup of oil, paint, hydraulic fluid, anti-freeze/coolant, brake fluid, gasoline and many other commonly spilled liquids. **TRANSFORM**'s unique characteristics allow it to float on water while absorbing dangerous and volatile liquids. Safe and convenient packaging allows for easy storage in any location, including vehicles.

DIRECTIONS

SUNRISE proposes various methods of applications of **TRANSFORM** to oil spills. For hard surface spills, just apply an adequate amount of **TRANSFORM** to the spill and stiff nylon broom the mixture back and forth, then sweep the residue into a dustpan. For oil and water spills, simply spread **TRANSFORM** onto floating oil and lightly agitate. Due to its bouyant, water-resistant qualities, **TRANSFORM** will bond to the waterborne oil spill and congeal into a solid or "biscuit" and then is easily removable by skimming with a strainer, leaving clean water.

FUNCTION

Ultra absorbent compound.

DESIGNED FOR

This product is designed for efficient clean-up of grease, paint, oil, fuel, and solvent spills.

FORMULATION

100% recycled materials.

FEATURES & BENEFITS

HIGH ABSORBENCY-Offsets more liquid. **DRY COMPOUND**-Ease of application and cleanup.
100% RECYCLED MATERIAL-Safe to use.

ADDITIONAL APPLICATIONS

None.

DEMO

Apply product to spill and demonstrate high rate of absorption.

TARGET ACCOUNTS

Municipal shops, mechanics, lumbermills, canning factories, food processing, gas stations.

FEDERAL REGISTRATION

None.

ALTERNATE PACKAGING

Bulk packaging and quarts.

SPECIAL CAUTIONS

None.

HMIS RATING or NFPA 704 HAZARD RATING
Extreme - 4 • High - 3 • Moderate - 2
Slight - 1 • Insignificant - 0

HEALTH	0
FLAMMABILITY	0
REACTIVITY	0



P.O. Box 10207
Reno, Nevada 89510
Fax: 775-359-6751
1-800-648-1153
775-359-8494

Product No.
4040 & 5069