

# NOT FOR RESALE



# SUNRISE

## ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

# ENVIRO-SOLVE

## LIFT STATION TREATMENT

## TRATAMIENTO DE LA ESTACIÓN DE ELEVACIÓN

**READ ENTIRE LABEL BEFORE USING.  
KEEP OUT OF REACH OF CHILDREN**

### SAFETY SECTION

SCAN FOR  
SDS & INFO



**TOXICITY 2**

**FIRE 1**

**REACTIVITY 0**

**SPECIAL NA**

### WARNING



- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

Ingredient Name	CAS#
Citrus Distillate	68847-72-3
Distillates, hydrotreated light	64742-47-6

### FEATURES AND BENEFITS

- ENVIRONMENTALLY SOUND
- NON-FUMING
- NO NOXIOUS ODOR
- BREAKS DOWN GREASE AND SLUDGE BUILD-UP

PRODUCT # 2108 • BATCH #

### TO REORDER CALL US @ 800.648.1153

This amazing new compound is designed to break down fats and sludge build-up in lift stations. Using citrus terpene technology **ENVIRO-SOLVE** combats common lift station problems in two ways. **ENVIRO-SOLVE** first acts as an odor mask. **ENVIRO-SOLVE** floats on top of the water acting as a cap for any unpleasant odor. The second function **ENVIRO-SOLVE** accomplishes is the breakdown of grease and sludge. As the water level in the lift station raises and lowers, **ENVIRO-SOLVE** cleans the sidewalls from grease and sludge as well as breaks down the grease floating on top. Put **ENVIRO-SOLVE** to work and watch your lift station problems disappear.

### DIRECTIONS

Ideally there should be a minimum 1/4 inch cap of **ENVIRO-SOLVE** floating in your lift station. To figure how much product should be added to acquire a 1/4 inch cap, use the following formula. Multiply the length(In Feet) x width(In Feet) x .020. Simply take your answer and multiply it by 7.5, this will give you how many gallons you need to add to cover your lift station with 1/4 inch of **ENVIRO-SOLVE**.

### SHIPPING/ DOT CLASSIFICATION

NA 1993, COMBUSTIBLE LIQUID  
N.O.S., (CONTAINS D- LIMONENE),  
PG III, CLASS 70

## SUNRISE ENVIRONMENTAL SCIENTIFIC



**800-648-1153 SUNRISENV.COM**  
**PO BOX 10207 - RENO, NEVADA 89510**