

KWIK KUT

CUTTING FLUID AND LUBRICANT
LUBRICANTE E INHIBIDOR DE FLUIDOS

KWIK KUT is a scientifically formulated cutting fluid that cools, lubricates and reduces friction during threading, drilling and tapping operations. KWIK KUT is colorless and thus permits constant viewing of the cutting area. It will not drip, eliminating mess and time consuming clean up.

- LONGER TOOL LIFE
- SPEEDS CUTTING
- REDUCES WASTE

DIRECTIONS

SPRAY directly on contact area of cutting implement and work piece while material is being processed.

SPRAYS BEST AT ROOM TEMPERATURE. Warm can to room temperature before spraying.

For additional information including SDS and Tech Data Sheet scan QR code here →



FEATURES:

- Extends the life of your drill bits and drilling tools
- Increases the speed of your cutting and tapping
- Reduces waste
- Pin point application
- Minimizes torque, Friction and Drag



KWIK KUT

KWIK KUT

CUTTING FLUID AND LUBRICANT FOR PRECISION

PRODUCT #1053

NET WEIGHT: 13 OZ (370 g)

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

CAUTIONS

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

INGREDIENTS

Naphthenic Distillate 64742-52-5, Acetone 67-64-1, Propellant 68-476-85-7

HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity: 1 Fire: 2 Reactivity: 0 Special: N.A

Hazard Symbol(s)



California Proposition 65



WARNING this product can expose you to chemicals including diethanolamine, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more info go to www.p65warnings.ca.gov

TRANSPORT INFORMATION

U.N. Number: UN 1950

U.N. Proper Shipping Name: Aerosol, Flammable
Transport Hazard Class(es): 2.1

Description: UN 1950, Aerosols, Flammable, Limited Quantity

SUNRISE ENVIRONMENTAL SCIENTIFIC

800-648-1153 SUNRISENV.COM



PO BOX 10207
RENO NV, 89510

Since 1975