


# SLING GLIDE



## SHAKER PAD LUBRICANT

LUBRICANT  
PRODUCTS



**SLING GLIDE II** is at the forefront of lubrication technology in the agricultural industry. This compound is designed to lubricate and protect rubber tree shaker slings, while at the same time preventing bark damage to the tree. In automatic water injection systems, **SLING GLIDE II** will be applied each time the sling clamp opens. The surface of the shaker sling will be re-coated with a protective film. **SLING GLIDE II** is also an excellent wire-pulling compound and tire mounting lubricant.

### FEATURES & BENEFITS

**HIGHLY DILUTABLE-** Lasts Longer.

**BUFFERS** - Safe on trees.

**SILICONE BLEND** - Increased lubrication.

### APPLICATIONS:

This compound is designed to prolong the life of shaker slings, and protect the bark on the tree.

### DIRECTIONS:

**AUTOMATIC INJECTION SYSTEMS:** For most applications, pour 1 quart of **SLING GLIDE II** into the shaker reservoir and add 25 gallons of water to it. Temperature, humidity and shaking conditions may require altering this dilution. When new shaker slings are installed it is recommended to pre-soak the working surface of the rubber with a 50% solution of **SLING GLIDE II** and water two or three times prior to installation.

**HAND APPLICATION:** Dilute **SLING GLIDE II** with water at a 1:1 ratio. Apply product with hand sprayer or brush once or twice every operation, or as conditions warrant.

### CUSTOMERS WHO USED THIS PRODUCT ALSO USED:

### FORMULATION:

Silicones, special lubrication compounds, surfactants.

### TARGET ACCOUNTS:

Any account where the use of shaker slings is necessary.

### SPECIAL CAUTIONS:

Pre-test on plastics.

### PACKAGING AVAILABILITY

2.5g and 55 g Drum

**PART #2021**

### QR CODE:



**WWW.SUNRISENV.COM**

P.O. Box 10207

Reno, Nevada 89510

Fax: 775-359-6751

1-800-648-1153

775-359-8494