

# ACRILAX

HIGH GLOSS FLOOR FINISH

ACABADO PARA PISOS CON BRILLO SUPERIOR

Now a high gloss without the hazard of slipperiness. Hospitals, invalid homes and department stores can now have beautiful, easy to maintain floors that are slip resistant, water resistant and black mark resistant. ACRILAX gives a higher gloss without any polishing or buffing. Easy to apply and maintain. ACRILAX brings out the natural and original true beauty of the floors. ACRILAX gives a beautiful finish to all floors such as asphalt tile, vinyl, plastic tile, linoleum, rubber tile, cork, composition, marble, terrazzo, as well as varnished wood floors. ACRILAX will not darken any floor. Will not water spot. SAFE AND EASY TO USE.

## DIRECTIONS:

Clean floor thoroughly by removing any old wax and soil. Rinse with clear water and allow to dry. Use a medium size string mop or lambs' wool applicator which has been rinsed in clear water and thoroughly wrung out. Allow to dry and then buff if desired. If a high gloss is desired, daily buffing with an electric polishing machine is recommended. For best results, allow the finish to set for 48 hours prior to buffing. Buff with a Palmetto brush. When used in California dilute 4:1 with water.

For additional information including SDS and Tech Data Sheet scan QR code here →




## PACKAGING

- 1 Gallon     15 Gallon     275 Gallon  
 5 Gallon     30 Gallon     Other:  
 6 Gallon     55 Gallon

## TRANSPORT INFORMATION

U.N. Number: Not applicable  
U.N. Proper Shipping Name: Liquid Wax Class 55  
Transport Hazard Class(es):  
Packing Group:



**SUNRISE**  
ENVIRONMENTAL SCIENTIFIC  
Blending the Demands of Industry and Environment

**ACRILAX**  
**HIGH GLOSS FLOOR FINISH**

**PART #2035**

READ ENTIRE LABEL BEFORE USING  
KEEP OUT OF REACH OF CHILDREN

## CAUTIONS

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent, cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

## INGREDIENTS

Acrylamide 76-06-1, Di Ethyl Ether 111-90-0

## HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity:0 Fire: 0 Reactivity: 0 Special: N.A

Hazard Symbol(s)



California Proposition 65



**WARNING** this product can expose you to chemicals including diethanolamine, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more info go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)



PO BOX 10207  
RENO NV, 89510

**Since 1975**