

SAFETY SECTION

WARNING: DO NOT INGEST. RESPIRATORY TRACT IRRITANT. MAY CAUSE SKIN IRRITATION OR BURN.

SCAN FOR SDS
& INFORMATION



TOXICITY	1
FIRE	3
REACTIVITY	0
SPECIAL	

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.



Ingredients: Polyetherfluorethane 9002-84-0, Mineral Oil Food Grade 64742-52-5, Aliphatic Petroleum Distillate 64742-89-8, Hydrocarbon Propellant 68-476-86-8

- **NSF RATED: H1**
- **MULTIPURPOSE**
- **PENETRATES**
- **WATER PROOFS**
- **NON-STAINING**



Nonfood Compounds
Program Listed H1,
Registration #155873



SUNRISE

ENVIRONMENTAL SCIENTIFIC
Blending the Demands of Industry and Environment

STAY SLICK FG

FOOD GRADE LUBRICANT

STAY STICK FG

SUNRISE'S STAY SLICK FG has been formulated for long-lasting lubrication and rust protection in food processing facilities. Translucent color allows for multiple application use without concern of dye contamination. Our premium synthetic compounds are designed to out-last similar spray greases by 3 times, therefore saving time and money. High temperature range (20-350 degrees) makes STAY SLICK FG the go-to option for all areas of a food processing facility.

DIRECTIONS: Spray a thin film on the surface to be lubricated or protected. To treat hard-to-reach areas, insert extension tube in spray tip. STAY SLICK FG will start forming into a grease in seconds. Allow 15 to 20 minutes for product to fully cure.

SUGGESTED USES:

- Tools
- Window Slides
- Hinges
- Power Mowers
- Tracks
- Metal Surfaces
- Floor Scrubbers
- General Marine Machinery

SUNRISE ENVIRONMENTAL SCIENTIFIC

800-648-1153

PO BOX 10207

RENO, NEVADA 89510



Proudly made
in the USA!



WWW.SUNRISENV.COM

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

PRODUCT #1114 NET WEIGHT: 16 OZ (454 g)