

# SAFETY SECTION

**WARNING:** DO NOT INGEST. RESPIRATORY TRACT IRRITANT. MAY CAUSE SKIN IRRITATION OR BURN.

SCAN FOR SDS  
& INFORMATION



<b>TOXICITY</b>	<b>1</b>
<b>FIRE</b>	<b>1</b>
<b>REACTIVITY</b>	<b>0</b>
<b>SPECIAL</b>	

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.



LIMITED QUANTITY

**Ingredients:** Polydimethyl Siloxane  
63148-62-9, Isoparaffinic Hydrocarbon  
64742-47-8, Propellant 68-476-86-8



Nonfood Compounds  
Program Listed H1  
(Registration #145310)

- HIGH QUALITY SYNTHETIC OILS
- ANTIWEAR AGENTS
- UNIQUE TACKINESS
- DIELECTRIC TO 35K VOLTS
- WATERPROOF FORMULATION

**CAUTION:** CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

**KEEP OUT OF REACH OF CHILDREN**

PRODUCT #1004 NET WEIGHT: 16.25 OZ (467.45 g)

  
**SUNRISE**  
ENVIRONMENTAL SCIENTIFIC  
Blending the Demands of Industry and Environment

# CHAIN GUARD F.G.

PREMIUM QUALITY FOOD GRADE CHAIN OIL

## CHAIN GUARD F.G.

**CHAIN GUARD FG** is manufactured from a combination of high quality HVI solvent-extracted dual hydrogenated paraffinic base oils and selected synthetic base oils. These are fortified with anti-wear agents and a tackiness agent to impart maximum anti-wear and clinging characteristics. **CHAIN GUARD FG** is recommended for lubrication of chains, rollers, and conveyors in industrial plants, food plants, and on agricultural equipment where quality lubricants should be used.

**DIRECTIONS:** Hold can 8 to 10 inches from surface and apply moderate amount of product (reapply as needed). Allow **CHAIN-GUARD FG** to "set" for 1 to 2 minutes before operating treated machinery. Use extension tube when pinpoint accuracy is needed.

### SUGGESTED USES:

- Ovens
- Chains
- Farm Equipment
- Food Processing Machinery
- Any Application Where a Heavy Bodied Lubricant is Desired

**SUNRISE ENVIRONMENTAL SCIENTIFIC**

800-648-1153

PO BOX 10207

RENO, NEVADA 89510



Proudly made  
in the USA!



WWW.SUNRISENV.COM