



F.F. EJ 1

**EXTRA STRENGTH
JET WASHING COMPOUND
FOR USE WITH ALL FERROUS AND
NON-FERROUS METAL CLEANING**

Read back panel before using.
KEEP OUT OF REACH OF CHILDREN

SAFETY SECTION

SCAN FOR
SDS & INFO



TOXICITY 2

FIRE 0

REACTIVITY 1

SPECIAL



! DANGER

- SKIN AND EYE IRRITANT
- RESPIRATORY TRACT IRRITANT
- SWALLOWING WILL CAUSE GASTROINTESTINAL IRRITATION



Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent, cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at

least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information. (CAS# 111-76-2, 10213-

Ingredient Name	CAS #
Sodium Hydroxide	1310-73-2
Sodium Metasilicate	6834-92-0
Trisodium Phosphate	10101-89-0
Sodium Bicarbonate	144-55-8
EDTA	64-02-8

PRODUCT #4026 • BATCH #

TO REORDER CALL US @ 800.648.1153

F.F. EJ-1

F.F. EJ-1 is a highly concentrated blend of surfactants, salts and detergents. This compound is ideal for stripping and degreasing all ferrous and non-ferrous metal parts normally cleaned in a Jet Washing machine. The unique blend of materials in F.F. EJ-1 enhances grease flotation, penetrates the most stubborn grease and carbon build-up while providing reduced incidence of nozzle blockage. **SUNRISE** recommends the use of our product **SWEET SPOT** in conjunction with F.F. EJ-1 **SWEET SPOT** may be introduced with this product to reduce foaming and odor build-up

DIRECTIONS: For optimum results, use between 2 and 4 ounces (by volume) of F.F. EJ-1 for every gallon of Jet Washer reservoir capacity. As make-up water is introduced into the washer, "spike" the solution as needed to ensure maximum cleaning and grease stratification. Maintain working temperature between 140 and 160 degrees F. or adjust temperature for work pieces. Use **SUNRISE'S SWEET SPOT** to reduce foam if necessary. **SWEET SPOT** will also enhance cleaning, brightening and rinsing of metallic parts. In addition, it will promote stratification of petroleum, reduce emulsification and assist skimmer disc performance. The use of F.F. EJ-1 in higher concentrations may be necessary for more difficult jobs and paint stripping. Do not use product on machined parts or where fine tolerances must be maintained. Check parts periodically for results.

SHIPPING/ DOT CLASSIFICATION

**UN 3262, CORROSIVE SOLID, BASIC INORGANIC, N.O.S
(CONTAINS SODIUM METASILICATE ANHYDROUS), 8, PG II CLASS 70**

SUNRISE ENVIRONMENTAL SCIENTIFIC

**800-648-1153 SUNRISENV.COM
PO BOX 10207 - RENO, NEVADA 89510**

