

## SAFETY SECTION

**WARNING:** DO NOT INGEST. RESPIRATORY TRACT IRRITANT. MAY CAUSE SKIN IRRITATION OR BURN.

SCAN FOR SDS  
& INFORMATION



**TOXICITY 1**

**FIRE 2**

**REACTIVITY 1**

**SPECIAL**



The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations.

Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information. (CAS# 64742-47-8/64742-96-7, 68-476-86-8).

Ingredient Name	CAS#
Isoparaffinic Hydrocarbon	64742-47-13
Aliphatic Petroleum Distillates	64742-47-8/64742-96-7
Propellant	68-476-86-8
Mineral Oil	647742-52-5

**SHIPPING/ DOT CLASSIFICATION**


## LIMITED QUANTITY

Since 1975...



Proudly made  
in the USA!

**CONTACT US:**  
800-648-1153  
775-359-8494  
PO BOX 10207  
RENO, NV 89510  
SUNRISENV.COM



## PENETRATING LUBRICANT LUBRICANTE PENETRANTE

- **ABILITY TO PENETRATE**
- **EASY TO USE AEROSOL PACKAGING**
- **CUTS RUST AND CORROSION**
- **DEEP PENETRATION OF CORRODED PARTS**

**CAUTION:** CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

**KEEP OUT OF REACH OF CHILDREN**

**PRODUCT #1013 NET WEIGHT: 16.25 OZ**

## AF3

**SHAKE WELL BEFORE USING!!**

**AF3** has a unique combination of ingredients that markedly reduce surface tension which permits rapid, deep penetration of corroded parts. **AF3** unique spray head permits spraying from any angle, allowing penetrant to reach areas otherwise inaccessible. **AF3** has an affinity to metal which aids penetration. Residual oil film lubricates and provides protection against subsequent corrosion. Penetrates and frees rusty parts such as bolts, nuts, lock mechanisms, speedometers, brake cables, fittings, etc. Helps eliminate the use of cold chisels, torches or saws. **AF3** has instant action that will cut rust, tar, gum, dirt, grease and corrosion.

**DIRECTIONS:** Spray **AF3** on object, saturate rusted or corroded area. Allow **AF3** to stand for several minutes. If necessary, tap fitting lightly and in extremely difficult cases of frozen parts re-apply as needed.

**TO REORDER CALL US AT 800.648.1153**

## SUGGESTED USES:

- **Bolts and Nuts**
- **Lock Mechanisms**
- **Speedometer**
- **Brake Cables**
- **Fittings**

**VISIT OUR WEBSITE AT [WWW.SUNRISENV.COM](http://WWW.SUNRISENV.COM)**

### ABOUT US...

Sunrise Environmental Scientific is a supplier of industrial chemical formulations to the Industrial, Institutional and Governmental marketplaces. In business since 1975, SES prides itself in manufacturing the highest quality chemical compounds available today.

Our wide market divergence and eclectic product line demand the utmost in production and sales efficiencies. We continually strive to "Blend the Demands of Industry and Environment", by complying with the most rigid air quality and environmental compatibility requirements in the country.