ZX WALL AND EQUIPMENT

SURFACE DE-SCALER AND CLEANER LIMPIADOR DE LA PARED Y DEL EQUIPO

ZX-WALL & EQUIPMENT CLEANER is designed for the removal of hard water and calcium build-up prone to the car wash industry. Once this is applied, it will leave a brilliant shine to walls and equipment.

DIRECTIONS

Test in an inconspicuous area before use. (When diluting. always add this product to water, NOT water to product.) Avoid splashing of product.

For general cleaning dilute at a ratio of 10 part water to one part ZX-WALL & EQUIPMENT CLEANER.

For heavier soiled areas dilute at a ratio of 5 parts water to 1 part ZX-WALL & EQUIPMENT CLEANER.

Make sure to apply from the bottom up. The solution may be either brushed on or sprayed on and allow dwell time until foam blanket occurs. Make sure to always rinse with water and re-apply if necessary. WARNING: Do not use with hot water

CAUTION: CONTAINS STRONG ACID

Harmful if swallowed. Do not get in eves, on skin, or on clothing. Prolonged or repeated exposure may cause dermatitis in sensitive individuals.

PACKAGING

1 Gallon 5 Gallon 6 Gallon

275 Gallon 15 Gallon 30 Gallon O Other: 55 Gallon





SUNRISE

Blending the Demands of Industry and Environment

PART #2179

READ ENTIRE LABEL BEFORE USING **KEEP OUT OF REACH OF CHILDREN**

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

INGREDIENTS

Hydrofluoric Acid 7664-39-3, Phosphoric Acid 7664-38-2

HAZARDS IDENTIFICATION

Signal Word: DANGER

Precautionary Statement(s):

Skin and eye irritant

Respiratory tract irritant

Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity:3 Fire: 0 Reactivity: 1 Special: N.A

Hazard Symbol(s)

17

C







PO BOX 10207 **RENO NV. 89510 Since 1975**