

CLEAR TAC FG

SYNTHETIC, HIGH-SPEED BEARING LUBRICANT

CLEAR TAC FG is the next great product in **SUNRISE'S** line of premium products made for the food processing industry. The name "**CLEAR TAC FG**" says it all! This translucent formulation is designed for areas where a high-speed, bearing lubricant is required. **CLEAR TAC FG** is multi-purpose, non-melting and waterproof. A high temperature range (-10 to 325°F) allows for use in a high friction environment.

DIRECTIONS:

Spray a thin film on the surface to be lubricated or protected. To treat hard to reach areas, use built in extension tube. **CLEAR TAC FG** will start forming into grease in seconds. Allow 5 to 10 minutes for product to fully cure.

For additional information including SDS and Tech Data Sheet scan QR code here →



FEATURES:

- **CHEMICAL RESISTANT**
- **NON-STAINING**
- **FOR HIGH SPEED APPLICATION**
- **REPELS WATER AND ICE**
- **LONG LASTING FORMULATION**

SUGGESTED USES:

- **Food Processing Machinery**
- **Chains**
- **Farm Equipment**
- **Fire Hydrants**
- **Water Lines**



CLEAR TAC FG

SYNTHETIC, HIGH-SPEED BEARING LUBRICANT

PRODUCT #1119

NET WEIGHT: 14.25 OZ (405 g)

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

CAUTIONS

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

INGREDIENTS

Isoparaffinic Hydrocarbon 64742-47-13, Hydrocarbon Propellant 68-476-86-8, Mineral Oil FG 8042-47-5

HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity: 1 Fire: 1 Reactivity: 0 Special: N.A

Hazard Symbol(s)



SUNRISE ENVIRONMENTAL SCIENTIFIC

800-648-1153 SUNRISENV.COM



PO BOX 10207
RENO NV, 89510

Since 1975