

STAY SLICK FG

FOOD GRADE LUBRICANT

CLEAR TAC FG is the next great product in **SUNRISE'S** line of premium products made for the food processing industry. The name "**CLEAR TAC FG**" says it all! This translucent formulation is designed for areas where a high-speed, bearing lubricant is required. **CLEAR TAC FG** is multi-purpose, non-melting and waterproof. A high temperature range (-10 to 325°F) allows for use in a high friction environment.

DIRECTIONS:

Spray a thin film on the surface to be lubricated or protected. To treat hard to reach areas, use built in extension tube. **CLEAR TAC FG** will start forming into grease in seconds. Allow 5 to 10 minutes for product to fully cure.

For additional information including SDS and Tech Data Sheet scan QR code here →



FEATURES:

- **NSF RATED: H1**
- **MULTI-PURPOSE**
- **PENETRATES**
- **WATER PROOFS**
- **NON-STAINING**

SUGGESTED USES:

- **Tools**
- **Window Slides**
- **Hinges**
- **Power Mowers**
- **Tracks**
- **Metal Surfaces**
- **Floor Scrubbers**
- **General Marine Machinery**



STAY SLICK FG

FOOD GRADE LUBRICANT

PRODUCT #1114

NET WEIGHT: 14.25 OZ (405 g)

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

CAUTIONS

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

INGREDIENTS

Polyetherfluorethane 9002-84-0, Mineral Oil Food Grade 64742-52-5, Aliphatic Petroleum Distillate 64742-89-8, Hydrocarbon Propellant 68-476-86-8

HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity:1 Fire: 3 Reactivity: 0 Special: N.A

Hazard Symbol(s)



Nonfood Compounds
158792

SUNRISE ENVIRONMENTAL SCIENTIFIC
800-648-1153 SUNRISENV.COM



PO BOX 10207
RENO NV, 89510

Since 1975