

NOT FOR RESALE



SUNRISE

ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

RELEASE 222

SHAKER PAD LUBRICANT

LUBRICANTE PARA GOMAS DE EXTRACTOR DE FRUTOS

**READ ENTIRE LABEL BEFORE USING.
KEEP OUT OF REACH OF CHILDREN**

SAFETY SECTION

SCAN FOR
SDS & INFO



TOXICITY 1

FIRE 3

REACTIVITY 0

SPECIAL NA



DANGER

- SKIN AND EYE IRRITANT
- RESPIRATORY TRACT IRRITANT
- MAY CAUSE SKIN BURN OR EYE DAMAGE



Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.



WARNING: This product can expose you to chemicals including benzene, which is known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient Name	CAS#
Aliphatic Petroleum Distillate	64742-89-8
Aliphatic Hydrocarbon	64742-49-0
Hexane	110-54-3
Isoparaffinic Hydrocarbon	64742-47-13
Benzene	71-43-2
Polydimethylsiloxane Silicone	63148-62-9

PRODUCT #2002 • BATCH #

TO REORDER CALL US @ 800.648.1153

RELEASE 222, is a clear silicone lubricant designed to lubricate and protect rubber tree shaker slings. This compound deeply penetrates into rubber and provides a slippery surface for reduced friction and heat build-up, while at the same time preventing bark damage to the tree. This clean, non-staining formula can be used with confidence to solve a multitude of problems relating to sticking, squeaking, etc. of rubber, leather, vinyl, metal, nylon, wood and painted surfaces.

DIRECTIONS

DIRECTIONS: Apply full strength product with hand sprayer, brush or **SUNRISE' "SURE SHOT"** sprayer to the working surface of the shaker sling. As the silicone impregnates the surface of the rubber, a shiny wet appearance will be maintained. Re-apply approximately once per hour or as conditions warrant. When new shaker slings are installed it is recommended to pre-soak the working surface of the rubber with **RELEASE 222** two or three times at 1-hour intervals prior to installation.

SHIPPING/ DOT CLASSIFICATION

UN 1268, PETROLEUM DISTILLATES, N.O.S., (CONTAINS NAPHTHA SOLVENT), FLAMMABLE LIQUID, 3, PG II, CLASS 70

SUNRISE ENVIRONMENTAL SCIENTIFIC



**800-648-1153 SUNRISENV.COM
PO BOX 10207 - RENO, NEVADA 89510**