

NOT FOR RESALE



SUNRISE

ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

ROLLER AND TIRE RELEASE

HIGH CONCENTRATE RELEASE AGENT

AGENTE DE ALTA LIBERACIÓN DE CONCENTRADO

**READ ENTIRE LABEL BEFORE USING.
KEEP OUT OF REACH OF CHILDREN**

SAFETY SECTION

SCAN FOR
SDS & INFO



TOXICITY 2

FIRE 0

REACTIVITY 0

SPECIAL NA



DANGER

- SKIN AND EYE IRRITANT
- RESPIRATORY TRACT IRRITANT
- SWALLOWING WILL CAUSE GASTRO-INTESTINAL IRRITATION



Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent, cough, hoarseness, or irritation. OSHA approved respirator recommended.

If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

Ingredient Name	CAS#
Fumed Silica	112945-52-5
Ethoxylated Nonyl Phenol Octylphenoxy Polyethoxy	9016-45-9
Sodium Xylene Sulphonate	1300-72-7
Sodium Sulfate	7757-82-6
Diethanolamine	111-42-2



WARNING: This product can expose you to chemicals including Diethanolamine, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

PRODUCT #2112 • BATCH #

TO REORDER CALL US @ 800.648.1153

ROLLER AND TIRE RELEASE

ROLLER AND TIRE RELEASE is a neutral pH, odorless liquid specially formulated for use in the paving industry on roller machines to prevent tar and asphalt build-up from rollers, tires and all other problematic equipment.

DIRECTIONS: ROLLER AND TIRE RELEASE should be diluted at a rate of 1 gallon of product per 90 gallons of water. Always make sure to add the product to the water to prevent too much foam.

CAUTION: Do not ingest. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. If skin is contacted, wash with soap and water. Avoid contact with eyes. If eyes are contacted, flush with water for 15 minutes. Consult Safety Data Sheet for further information.

SHIPPING/ DOT CLASSIFICATION

LIQUID CLEANER CLASS 55

SUNRISE ENVIRONMENTAL SCIENTIFIC



800-648-1153 SUNRISENV.COM
PO BOX 10207 - RENO, NEVADA 89510