

ALL FREE II

LUBRICANT
LUBRICANTE

ALL FREE II has a unique combination of ingredients that markedly reduce surface tension which permits rapid, deep penetration of corroded parts. ALL FREE II has an affinity to metal which aids penetration. Residual oil film lubricates and provides protection against subsequent corrosion. Penetrates and frees rusty parts such as bolts, nuts, lock mechanisms, speedometers, brake cables, fittings, etc. Helps eliminate the use of cold chisels, torches or saws. ALL FREE II has instant action that will cut rust, tar, gum, dirt, grease and corrosion.

DIRECTIONS

Apply ALL FREE II to object; saturate rusted or corroded area. Allow ALL FREE II to stand for several minutes. If necessary, tap fitting lightly, and in extremely difficult cases of frozen parts, re-apply as needed.

PACKAGING

- 1 Gallon 15 Gallon 275 Gallon
 5 Gallon 30 Gallon Other:
 6 Gallon 55 Gallon

For additional information including SDS and Tech Data Sheet scan QR code here →



TRANSPORT INFORMATION

U.N. Number: Not applicable
U.N. Proper Shipping Name: Lubricant Class 55
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable



ALL FREE II

PENETRATES - LUBRICATES - CHAIN LUBE

PART #2036

READ ENTIRE LABEL BEFORE USING
KEEP OUT OF REACH OF CHILDREN

CAUTIONS

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent, cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

INGREDIENTS

Isoparaffinic Hydrocarbon 64742-47-13, Aliphatic Hydrocarbon 64742-47-8, Paraffinic Hydrocarbon 64741-88-4, Mineral Oil 647742-52-5

HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity:1 Fire: 1 Reactivity: 1 Special: N.A

Hazard Symbol(s)



PO BOX 10207
RENO NV, 89510

Since 1975