

# POWER PLUS

AMMONIATED WAX STRIPPER  
REMOVEDOR DE CERAS PARA PISOS

**POWER PLUS** has been designed for todays new, more durable polymer finishes. It unlocks those cross linked polymers to provide easy stripping of wax. **POWER PLUS** has many other uses as well, cleans soap scum and wax from conveyor belts, assembly lines, degreases metal surfaces, concrete floors, walls, grills, fans, etc.

## DIRECTIONS:

Dilute **POWER PLUS** with one part product to 2 parts water. Liberally spray, mop or sponge onto surface to be treated. Let sit 10 minutes, scrub with stripping pad or available appliance. Mop up surface - spot strip if necessary. Flood with clean rinse water, mop up surface, gives truly professional results.

For additional information including SDS and Tech Data Sheet scan QR code here →



## PACKAGING

- 1 Gallon     15 Gallon     275 Gallon  
 5 Gallon     30 Gallon     Other:  
 6 Gallon     55 Gallon

## TRANSPORT INFORMATION

U.N. Number: Not applicable  
U.N. Proper Shipping Name: Limited Quantity Class 85  
Transport Hazard Class(es):  
Packing Group:



# POWER PLUS AMMONIATED WAX STRIPPER

## PART #2058

READ ENTIRE LABEL BEFORE USING  
KEEP OUT OF REACH OF CHILDREN

## CAUTIONS

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent, cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

## INGREDIENTS

2-Butoxyethanol 111-76-2, Caustic Potash 1310-58-3, Sodium Metasilicate 6834-92-0, Ammonium Hydroxide 1336-21-6, Nonylphenol Ethoxlate 9016-45-9

## HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

## H.M.I.S.

Toxicity:2 Fire: 0 Reactivity: 1 Special: N.A

## Hazard Symbol(s)



PO BOX 10207  
RENO NV, 89510

Since 1975